

# Wire-O® Bind

The Semi-Automatic Wire-O® Binder provides high-speed Wire-O® finishing 'on-demand' from cost-efficient spools.

At 500-1000 books per hour, the Wire-O® Binder is super fast, yet simple to operate with all size and format setups instantly adjustable by user-friendly 'touch screen' electronic controls.

The automatic functions cut, feed and position the wire for insertion; then sends the document to a patented closing unit that now accurately positions the document, without the need for stops or paper guides.

The versatile Wire-O® Binder is designed to work alongside the highly successful Alpha Doc® and DocuPunch® Automatic Punching Machines, accurately finishing a wide variety of documents, including oversize covers & tabbed sheets, for all Wire-O® sizes up to 1-1/4". Together, they are the perfect high-speed Wire-O® finishing solution for today's modern in-plant, digital and 'on-demand' printing environments, where ease-of-use, versatility and productivity are a must.



## Features:

- **Easy to Use** - Automatically cuts wire to length, feeds and positions wire for insertion; accurately sends book to patented closing station, and delivers book to standard pile reception unit. No special training required.
- **Touch Screen Controls** - All size and format functions are setup and instantly adjustable by user-friendly 'touch screen' electronic controls. Wire-O® size changeovers in 2-5 minutes.
- **Outstanding Productivity** - Output rates of 500-1000 books per hour, depending on format, paper quality and operator skill.
- **Versatile** - Finishes all 3:1" & 2:1" pitch Wire-O® sizes from 1/4" to 1-1/4".
- **Hanger Feeder** - The optional hanger feeder is a simple "plug and play" unit. It inserts calendar hangers from reeled hanger spool or from loose hangers.
- **Efficient** - Finishes from economical Wire-O® spools. Automatic features reduce setup waste.
- **Adaptable** - Finishes flush cut and overhanging covers, as well as extended index tabs.
- **Ergonomic Design** - Operator-friendly with large table-top workstation helps reduce fatigue. Cycles with push-button or foot pedal switch.
- **Spool Loading** - At floor level. Wire power lifted into position.
- **Binding Format** - Min: 2" x 3.75"; Max: 14" x 14"
- **Wire-O® Diameters** - All 3:1" & 2:1" pitch from 1/4" to 1-1/4"
- **Skip Binding** - 3:1 pitch: 2 x 8 loop minimum / 2 x 19 loop maximum with a spacing of 3 loops minimum and 25 loops maximum.  
2:1 pitch: 2 x 5 loops minimum / 2 x 13 loop maximum with a spacing of 2 loops minimum and 18 loops maximum.
- **Simple Installation** - Caster wheels allow easy placement. No air required.
- **Voltage Requirements** - 110V single phase 60Hz or 220-240V single phase 50Hz available
- **Dimensions** - 4' H x 7' W x 2.5' D
- **Weight** - Approx. 625 lbs. unpacked

**Spiral**   
Where Finishing Begins.™

[www.spiralbinding.com](http://www.spiralbinding.com)  
800.631.3572